NSN 5320-01-351-9870

Pin-rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-351-9870

| Thread Direction: |
|---|
| Right-hand |
| Fastener Length: |
| Between 48.8 millimeters and 49.3 millimeters |
| Head Style: |
| Flush countersunk |
| Width Between Flats: |
| Between 3.2 millimeters and 3.3 millimeters |
| Shank Diameter: |
| Between 8.97 millimeters and 8.99 millimeters |
| Shank Style: |
| Pin-rivet, straight, threaded |
| Head Major Diameter: |
| Between 13.6 millimeters and 13.7 millimeters |
| Grip Length: |
| Between 34.9 millimeters and 35.1 millimeters |
| Thread Size: |
| 9.0 millimeters |
| Thread Pitch In Millimeters: |
| 0.75 |
| Shear Strength: |
| 83300 double newtons per square millimeter |
| Countersink Angle: |
| 100.0 degrees |
| Thread Tolerance Class: |
| 4h external |
| Material: |
| Titanium alloy uns r56400 |
| Thread Series Designator: |
| lso m |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A528u0 |
| |
| |