

View Online at <https://aerobasegroup.com/nsn/5320-01-352-2091>

Head Style:

Countersunk (tubular)

Hole Diameter:

Between 0.1560 inches and 0.1600 inches

Shank Style:

Tubular

Head Major Diameter:

Between 0.2760 inches and 0.2900 inches

Grip Length:

Between 0.5010 inches and 0.5620 inches

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Material:

Steel comp 8740 boltiron alloy 660 locking ring or steel comp 304 locking ringaluminum alloy 5056 sleeve

Material Specification:

Ams 6322 assn standard single material response boltams 5731 assn standard 1st material response locking ring or ams 5639 assn standard 2nd material response locking ringqq-a-430 federal specification single material response sleeve

Surface Treatment:

Cadmium bolt and chromate boltpassivate locking ringchromate sleeve

Surface Treatment Specification:

Qq-p-416, ty ii, cl 2 federal specification single treatment response boltqq-p-35 federal specification single treatment response locking ringmil-c-5541 military specification single treatment response sleeve

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A040a0

Mil-std (military Standard):

Mil-c-5541 spec.