

View Online at <https://aerobasegroup.com/nsn/5320-01-352-2100>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 4.4585 inches and 4.4835 inches

**Head Style:**

Err-090

**Head Height:**

Between 0.268 inches and 0.280 inches

**Shank Diameter:**

Between 0.7010 inches and 0.7015 inches

**Shank Style:**

Blind rivet, nut and bolt assembly

**Head Major Diameter:**

Between 1.079 inches and 1.096 inches

**Lubrication:**

Dry film and cetyl alcohol

**End Application:**

C-17

**Grip Length:**

Between 3.6825 inches and 3.6975 inches

**Thread Qty Per Inch (tpi):**

18

**Min. Tensile Strength (psi):**

34800 pounds per square inch

**Thread Size:**

0.5625 inches

**Shear Strength:**

47200 double pounds per square inch

**Product Name:**

Pin-riquet, threaded

**Special Features:**

Sleeve included

**Material:**

Titanium alloy uns r56400 bolt

**Material Specification:**

Astm-a269 assn standard single material response sleeve or mil-t-8504 military specification single material response sleeve

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0

**Mil-std (military Standard):**

Mil-t-8504 spec.