

View Online at <https://aerobasegroup.com/nsn/5320-01-352-2100>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 4.4585 inches and 4.4835 inches

Head Style:

Err-090

Head Height:

Between 0.268 inches and 0.280 inches

Shank Diameter:

Between 0.7010 inches and 0.7015 inches

Shank Style:

Blind rivet, nut and bolt assembly

Head Major Diameter:

Between 1.079 inches and 1.096 inches

Lubrication:

Dry film and cetyl alcohol

End Application:

C-17

Grip Length:

Between 3.6825 inches and 3.6975 inches

Thready Qty Per Inch (tpi):

18

Min. Tensile Strength (psi):

34800 pounds per square inch

Thread Size:

0.5625 inches

Shear Strength:

47200 double pounds per square inch

Product Name:

Pin-rivet, threaded

Special Features:

Sleeve included

Material:

Titanium alloy uns r56400 bolt

Material Specification:

Astm-a269 assn standard single material response sleeve or mil-t-8504 military specification single material response sleeve

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-t-8504 spec.