NSN 5320-01-352-2102

Blind Rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-352-2102

Thread Class:
3a
Thread Direction:
Right-hand
Fastener Length:
Between 3.426 inches and 3.451 inches
Head Style:
Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)
Shank Diameter:
Between 0.6785 inches and 0.6795 inches
Head Major Diameter:
Between 1.1310 inches and 1.2260 inches
Expansion Device:
Threaded stem
Lubrication:
Solid film and cetyl alcohol
Grip Length:
Between 2.615 inches and 2.630 inches
Thready Qty Per Inch (tpi):
18
Min. Tensile Strength (psi):
34800 pounds per square inch
Thread Size:
0.5625 inches
Shear Strength:
47200 double pounds per square inch
Countersink Angle:
Between 102.0 degrees and 103.0 degrees
Material:
Titanium alloy uns r56400 bolt
Material Specification:
Mil-t-8504 military specification single material response sleeve
Surface Treatment:
Passivate bolt
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response bolt
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:

NSN 5320-01-352-2102

Blind Rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-t-8504 spec.

