

View Online at <https://aerobasegroup.com/nsn/5320-01-352-2199>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 1.5000 inches and 1.5200 inches

**Head Style:**

Err-090

**Head Height:**

Between 0.0930 inches and 0.1050 inches

**Width Between Flats:**

Between 0.1895 inches and 0.1930 inches

**Shank Diameter:**

Between 0.4365 inches and 0.4370 inches

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

Between 0.6410 inches and 0.6760 inches

**Lubrication:**

Cetyl alcohol

**Grip Length:**

Between 0.8700 inches and 0.8800 inches

**Thready Qty Per Inch (tpi):**

20

**Min. Tensile Strength (psi):**

12100 pounds per square inch

**Thread Size:**

0.4380 inches

**Shear Strength:**

95000 single pounds per square inch

**Material:**

Titanium alloy uns r56400

**Material Specification:**

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A528u0