# NSN 5320-01-352-3410

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-352-3410



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

# Fastener Length:

Between 4.1600 inches and 4.1800 inches

#### Head Style:

Cooper's

#### **Head Height:**

Between 0.0900 inches and 0.1030 inches

#### Width Between Flats:

Between 0.1582 inches and 0.1617 inches

#### Shank Diameter:

Between 0.3740 inches and 0.3745 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 1.1000 inches and 1.2229 inches

# Lubrication:

Cetyl alcohol

# Grip Length:

Between 3.6200 inches and 3.6300 inches

#### Thready Qty Per Inch (tpi):

24

#### Min. Tensile Strength (psi):

95000 pounds per square inch

# Thread Size:

0.3750 inches

# **Countersink Angle:**

Between 155.0 degrees and 157.0 degrees

#### Material:

Titanium alloy uns r56400

#### Material Specification:

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

#### Thread Series Designator:

Unjf

# Shelf Life:

N/a

# Unit Of Measure:

--

# Demilitarization:

No

# NSN 5320-01-352-3410

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

