

View Online at <https://aerobasegroup.com/nsn/5320-01-352-3410>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 4.1600 inches and 4.1800 inches

**Head Style:**

Cooper's

**Head Height:**

Between 0.0900 inches and 0.1030 inches

**Width Between Flats:**

Between 0.1582 inches and 0.1617 inches

**Shank Diameter:**

Between 0.3740 inches and 0.3745 inches

**Shank Style:**

Pin-riquet, straight, threaded

**Head Major Diameter:**

Between 1.1000 inches and 1.2229 inches

**Lubrication:**

Cetyl alcohol

**Grip Length:**

Between 3.6200 inches and 3.6300 inches

**Thread Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

95000 pounds per square inch

**Thread Size:**

0.3750 inches

**Countersink Angle:**

Between 155.0 degrees and 157.0 degrees

**Material:**

Titanium alloy uns r56400

**Material Specification:**

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A528u0