## NSN 5320-01-352-3411

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-352-3411 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 2.8850 inches and 2.9050 inches **Head Style:** Cooper's **Head Height:** Between 0.0630 inches and 0.0670 inches Width Between Flats: Between 0.0947 inches and 0.0987 inches **Shank Diameter:** Between 0.2490 inches and 0.2495 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.7000 inches and 0.8000 inches Lubrication: Cetyl alcohol **Grip Length:** Between 2.4950 inches and 2.5050 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 95000 pounds per square inch **Thread Size:** 0.2500 inches **Countersink Angle:** Between 155.0 degrees and 157.0 degrees Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5320-01-352-3411

Pin-rivet - Page 2 of 2



Fiig:

A528u0