## NSN 5320-01-352-3412

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-352-3412 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 3.2600 inches and 3.2800 inches **Head Style:** Cooper's **Head Height:** Between 0.0630 inches and 0.0870 inches Width Between Flats: Between 0.0947 inches and 0.0967 inches **Shank Diameter:** Between 0.2490 inches and 0.2495 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.7000 inches and 0.8000 inches Lubrication: Cetyl alcohol **Grip Length:** Between 2.8700 inches and 2.8800 inches Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.2500 inches **Shear Strength:** 95000 single pounds per square inch **Countersink Angle:** Between 155.0 degrees and 157.0 degrees Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

No

## NSN 5320-01-352-3412

Pin-rivet - Page 2 of 2



Fiig:

A528u0