## NSN 5320-01-352-8502

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-352-8502

Thread Class:
3a
Thread Direction:
Right-hand
Fastener Length:
Between 0.5300 inches and 0.5500 inches
Head Style:
Err-090
Head Height:
Between 0.0450 inches and 0.0550 inches
Hole Diameter:
Between 0.0104 inches and 0.0119 inches
Shoulder Diameter:
Between 0.1885 inches and 0.1895 inches
Shoulder Length:
Between 0.2450 inches and 0.2550 inches
Shank Diameter:
0.1900 inches
Shank Style:
Err-090
Head Major Diameter:
Between 0.2950 inches and 0.3150 inches
Hole Depth:
Between 0.1150 inches and 0.1350 inches
Lubrication:
Cetyl alcohol
Grip Length:
Between 0.2450 inches and 0.2550 inches
Thready Qty Per Inch (tpi):
32
Thread Size:
0.1900 inches
Shear Strength:
95000 single pounds per square inch
Material:
Titanium alloy uns r56400
Material Specification:
Ams 4967 assn standard single material response or ams 4928 assn standard single material response
Surface Treatment:
Aluminum and chromate
Surface Treatment Specification:
Mil-c-83488, type 2, cl 3 military specification single treatment response

## NSN 5320-01-352-8502

Pin-rivet - Page 2 of 2



Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A528u0
Mil-std (military Standard):

Mil-c-83488 spec.