

View Online at <https://aerobasegroup.com/nsn/5320-01-352-8502>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 0.5300 inches and 0.5500 inches

**Head Style:**

Err-090

**Head Height:**

Between 0.0450 inches and 0.0550 inches

**Hole Diameter:**

Between 0.0104 inches and 0.0119 inches

**Shoulder Diameter:**

Between 0.1885 inches and 0.1895 inches

**Shoulder Length:**

Between 0.2450 inches and 0.2550 inches

**Shank Diameter:**

0.1900 inches

**Shank Style:**

Err-090

**Head Major Diameter:**

Between 0.2950 inches and 0.3150 inches

**Hole Depth:**

Between 0.1150 inches and 0.1350 inches

**Lubrication:**

Cetyl alcohol

**Grip Length:**

Between 0.2450 inches and 0.2550 inches

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.1900 inches

**Shear Strength:**

95000 single pounds per square inch

**Material:**

Titanium alloy uns r56400

**Material Specification:**

Ams 4967 assn standard single material response or ams 4928 assn standard single material response

**Surface Treatment:**

Aluminum and chromate

**Surface Treatment Specification:**

Mil-c-83488, type 2, cl 3 military specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0

**Mil-std (military Standard):**

Mil-c-83488 spec.