

View Online at <https://aerobasegroup.com/nsn/5320-01-353-1417>

**Head Style:**

Countersunk (tubular)

**Hole Diameter:**

0.1560 inches

**Shank Diameter:**

Between 0.1560 inches and 0.1600 inches

**Shank Style:**

Tubular

**Head Major Diameter:**

Between 0.2760 inches and 0.2900 inches

**Grip Length:**

Between 0.4380 inches and 0.5000 inches

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Material:**

Steel comp 8740 boltiron alloy 660 locking ring or steel comp 1030 locking ringaluminum alloy 5056 sleeve

**Material Specification:**

Ans 6322 assn standard single material response boltams 5731 assn standard 1st material response locking ring or ams 5639 assn standard 2nd material response locking ringq-q-a-430 federal specification single material response sleeve

**Surface Treatment:**

Cadmium bolt and chromate boltpassivate locking ringchromate sleeve

**Surface Treatment Specification:**

Q-q-p-416, ty ii, cl 2 federal specification single treatment response boltq-q-p-35 federal specification single treatment response locking ringmil-c-5541 military specification single treatment response sleeve

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0

**Mil-std (military Standard):**

Mil-c-5541 spec.