

View Online at <https://aerobasegroup.com/nsn/5320-01-353-1420>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 2.8650 inches and 2.8850 inches

**Head Style:**

Cooper's

**Head Height:**

Between 0.0800 inches and 0.0840 inches

**Width Between Flats:**

Between 0.1270 inches and 0.1290 inches

**Shank Diameter:**

Between 0.3115 inches and 0.3120 inches

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

Between 0.8670 inches and 0.9010 inches

**Lubrication:**

Cetyl alcohol

**Grip Length:**

Between 2.3700 inches and 2.3800 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

95000 pounds per square inch

**Thread Size:**

0.3125 inches

**Countersink Angle:**

Between 155.0 degrees and 157.0 degrees

**Material:**

Titanium alloy uns r56400

**Material Specification:**

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0