

View Online at <https://aerobasegroup.com/nsn/5320-01-353-3669>

Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

Between 0.1965 inches and 0.1985 inches

Shank Style:

Blind rivet, nut and bolt (assembly)

Head Major Diameter:

Between 0.3780 inches and 0.3850 inches

Expansion Device:

Threaded stem

Lubrication:

Dry film or cetyl alcohol or carbo wax or paraffin wax

Grip Length:

Between 0.1500 inches and 0.2000 inches

Countersink Angle:

Between 129.0 degrees and 131.0 degrees

Material:

Titanium alloy uns r56400 nutsteel comp 304 sleeveiron alloy 660 stem

Material Specification:

Ams 4928 assn standard single material response nut or ams 4967 assn standard single material response nutams 5639 assn standard single material response sleeveams 5731 assn standard single material response stem or ams 5732 assn standard single material response stem or ams 5737 assn standard single material response stem

Surface Treatment:

Passivate sleevepassivate stem

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response sleeveqq-p-35 federal specification single treatment response stem

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0