

View Online at <https://aerobasegroup.com/nsn/5320-01-353-6147>

**Fastener Length:**

0.448 inches

**Head Style:**

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

**Shank Diameter:**

0.1240 inches

**Shank Style:**

Self-plugging mechanically locked stem

**Head Major Diameter:**

Between 0.1880 inches and 0.1960 inches

**Expansion Device:**

Plain stem-type t

**Grip Length:**

Between 0.2510 inches and 0.3120 inches

**Countersink Angle:**

Between 98.5 degrees and 101.5 degrees

**Material:**

Iron alloy 660 locking ring or nickel alloy k-500 locking ring or nickel alloy r-405 locking ringnickel alloy r-405 sleeve or nickel alloy k-500 sleeveiron alloy 660 stem

**Material Specification:**

Ams 5737 assn standard 1st material response locking ring or qq-n-281 federal specification 2nd material response locking ring or qq-n-281 federal specification 3rd material response locking ringqq-n-281 assn standard single material response sleeveams 5737 assn standard single material response stem

**Surface Treatment:**

Passivate stem

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response stem

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0