## NSN 5320-01-353-9349

Blind Rivet - Page 1 of 1

Demilitarization:

No Fiig: A040a0



View Online at https://aerobasegroup.com/nsn/5320-01-353-9349
Fastener Length:
Between 0.8030 inches and 0.8230 inches
Head Style:
Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)
Shank Diameter:
Between 0.2490 inches and 0.2530 inches
Shank Style:
Self-plugging mechanically locked stem
Head Major Diameter:
Between 0.4270 inches and 0.4800 inches
Expansion Device:
Serrated stem-type w
Lubrication:
Dry film or paraffin wax or carbo wax or cetyl alcohol
Grip Length:
Between 0.5630 inches and 0.6250 inches
Countersink Angle:
Between 99.5 degrees and 101.5 degrees
Material:
Nickel alloy r-405 locking ringiron alloy 660 sleeveiron alloy 660 stem
Material Specification:
Qq-n-281 federal specification single material response locking ringams 5737 assn standard single material response sleeveams 5731 assn
standard single material response stem
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Shelf Life:
N/a
Unit Of Measure: