

View Online at <https://aerobasegroup.com/nsn/5320-01-353-9993>

**Head Style:**

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

**Shank Diameter:**

Between 0.3725 inches and 0.3745 inches

**Shank Style:**

Threaded self-plugging shank w/sleeve

**Head Major Diameter:**

0.696 inches

**Expansion Device:**

Threaded stem

**Lubrication:**

Dry film or paraffin wax or cetyl alcohol

**Grip Length:**

Between 0.220 inches and 0.281 inches

**Features Provided:**

Drive nut

**Hardness Rating:**

39.0 rockwell c nut and 43.0 rockwell c nut

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Special Features:**

Drive nut steel, color coded gold, with a corrosion retardent coating

**Material:**

Steel comp 4130 nut or steel comp 4140 nut or steel comp 8740 nut

**Material Specification:**

Mil-s-6758 military specification 1st material response nut or mil-s-5626 military specification 2nd material response nut or mil-s-6049 military specification 3rd material response nut

**Surface Treatment:**

Passivate sleeve and cadmium sleeve

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification single treatment response nut

**Specification Data:**

80205-nas1670 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0

**Mil-std (military Standard):**

Mil-s-6758 spec.