## NSN 5320-01-354-0004

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-354-0004

Head Style:
Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)
Shank Diameter:
Between 0.274 inches and 0.276 inches
Shank Style:
Threaded self-plugging shank w/sleeve
Head Major Diameter:
0.430 inches
Expansion Device:
Threaded stem
Grip Length:
Between 0.282 inches and 0.344 inches
Features Provided:
Self-locking
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Material:
Steel comp 4140 bolt or steel comp 8740 bolt or steel comp 4130 bolt
Material Specification:
Qq-s-763 federal specification 1st material response sleeve or ams 5639 assn standard 2nd material response sleeve or ams 5641 assr
standard 3rd material response sleeve
Surface Treatment:
Cadmium sleeve
Surface Treatment Specification:
Qq-p-416, type 2, cl 2 federal specification all treatment responses bolt
Specification Data:
80205-nas1754 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A040a0

Mil-std (military Standard):

Mil-s-5626 spec.