

View Online at <https://aerobasegroup.com/nsn/5320-01-354-0016>

Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

Between 0.3250 inches and 0.3270 inches

Shank Style:

Threaded self-plugging shank w/sleeve

Head Major Diameter:

0.577 inches

Expansion Device:

Threaded stem

Lubrication:

Dry film or paraffin wax or cetyl alcohol

Grip Length:

Between 1.220 inches and 1.281 inches

Features Provided:

Drive nut

Hardness Rating:

39.0 rockwell c bolt and 43.0 rockwell c bolt

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Special Features:

Drive nut steel, color coded gold, with a corrosion retardent coating

Material:

Steel comp 4140 bolt or steel comp 8740 bolt or steel comp 4130 bolt

Material Specification:

Qq-a-225/9, t6 federal specification single material response nut

Surface Treatment:

Passivate sleeve and cadmium sleeve or passivate sleeve and cadmium sleeve and chromate sleeve

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response bolt

Specification Data:

80205-nas1674 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-s-5626 spec.