NSN 5320-01-354-0039



Blind Rivet - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5320-01-354-0039 **Head Style:** Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer) **Shank Diameter:** Between 0.178 inches and 0.180 inches **Shank Style:** Threaded self-plugging shank w/sleeve **Head Major Diameter:** 0.259 inches **Expansion Device:** Threaded stem **Grip Length:** Between 0.094 inches and 0.156 inches **Features Provided:** Self-locking **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Steel comp 4140 bolt or steel comp 8740 bolt or steel comp 4130 bolt **Material Specification:** Qq-s-763 federal specification 1st material response sleeve or ams 5639 assn standard 2nd material response sleeve or ams 5641 assn standard 3rd material response sleeve **Surface Treatment:** Cadmium sleeve **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification all treatment responses bolt **Specification Data:** 80205-nas1754 professional/industrial association standard Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No Fiig:

A040a0

710 1000

Mil-std (military Standard):

Mil-s-5626 spec.