

View Online at <https://aerobasegroup.com/nsn/5320-01-354-0914>

Fastener Length:

Between 0.1240 inches and 0.1280 inches

Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

Between 0.1240 inches and 0.1280 inches

Shank Style:

Self-plugging mechanically locked stem

Head Major Diameter:

Between 0.1880 inches and 0.1980 inches

Grip Length:

Between 0.3130 inches and 0.3750 inches

Countersink Angle:

Between 98.5 degrees and 101.0 degrees

Material:

Iron alloy 660 locking ring or nickel alloy r-405 locking ring or nickel alloy k-500 locking ringnickel alloy r-405 sleeve or nickel alloy k-500 sleeveiron alloy 660 stem

Material Specification:

Ams 5737 assn standard 1st material response locking ring or qq-n-281 federal specification 2nd material response locking ring or qq-n-281 federal specification 3rd material response locking ringqq-n-281 federal specification single material response sleeveams 5737 assn standard single material response stem

Surface Treatment:

Passivate stem

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response stem

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0