

View Online at <https://aerobasegroup.com/nsn/5320-01-354-2547>

Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

Between 0.1880 inches and 0.1920 inches

Shank Style:

Blind rivet, nut and bolt (assembly)

Head Major Diameter:

Between 0.2800 inches and 0.2980 inches

Expansion Device:

Plain stem-type t

Grip Length:

Between 0.1260 inches and 0.1870 inches

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Material:

Steel comp 8740 locking ringaluminum alloy 5056 sleeveiron alloy 660 stem or steel comp 304 stem

Material Specification:

Ams 5731 assn standard single material response locking ring or ams 5639 assn standard single material response locking ringqq-a-340 federal specification single material response sleeveams 6322 assn standard single material response stem

Surface Treatment:

Passivate locking ringchromate sleeve cadmium stem and chromate stem

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response locking ringmil-c-5541 military specification single treatment response sleeveqq-p-416, type 2, cl 2 federal specification single treatment response stem

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-c-5541 spec.