

View Online at <https://aerobasegroup.com/nsn/5320-01-354-2547>

**Head Style:**

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

**Shank Diameter:**

Between 0.1880 inches and 0.1920 inches

**Shank Style:**

Blind rivet, nut and bolt (assembly)

**Head Major Diameter:**

Between 0.2800 inches and 0.2980 inches

**Expansion Device:**

Plain stem-type t

**Grip Length:**

Between 0.1260 inches and 0.1870 inches

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Material:**

Steel comp 8740 locking ringaluminum alloy 5056 sleeveiron alloy 660 stem or steel comp 304 stem

**Material Specification:**

Ams 5731 assn standard single material response locking ring or ams 5639 assn standard single material response locking ringqq-a-340 federal specification single material response sleeveams 6322 assn standard single material response stem

**Surface Treatment:**

Passivate locking ringchromate sleeve cadmium stem and chromate stem

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response locking ringmil-c-5541 military specification single treatment response sleeveqq-p-416, type 2, cl 2 federal specification single treatment response stem

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0

**Mil-std (military Standard):**

Mil-c-5541 spec.