NSN 5320-01-354-6656

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-354-6656 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 2.627 inches and 2.647 inches **Head Style:** Flush countersunk **Shank Diameter:** Between 0.3735 inches and 0.3745 inches **Shank Style:** Err-090 **Head Major Diameter:** Between 0.5554 inches and 0.5604 inches **Grip Length:** Between 2.057 inches and 2.067 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch **Thread Size:** 0.375 inches **Countersink Angle:** 100.0 degrees Material: Steel **Material Specification:** Mil-s-5000 military specification single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq0p-416, tyii, cl3 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 73197-hl51-12-33 professional/industrial association specification Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 5320-01-354-6656

Pin-rivet - Page 2 of 2



Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5000 spec.