

View Online at <https://aerobasegroup.com/nsn/5320-01-355-0232>

Fastener Length:

0.5310 inches

Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

Between 0.2580 inches and 0.2600 inches

Shank Style:

Self-plugging mechanically locked stem

Head Major Diameter:

0.5070 inches

Expansion Device:

Serrated stem-type w

Grip Length:

Between 0.2810 inches and 0.3450 inches

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Material:

Steel comp 1010 mechanical lock or steel comp 1020 mechanical lock or steel comp 1144 mechanical lock or steel comp 4037 mechanical lock or steel comp 4130 mechanical locksteel comp e4340 sleeve or steel comp 4027 sleeve or steel comp 4037 sleeve or steel comp 4130 sleeve or steel comp 4140 sleeve or steel comp 4150 sleeve or steel comp 4340 sleeve or steel comp 4620 sleeve or steel comp 4815 sleeve or steel comp 6150 sleeve or steel comp 8615 sleeve or steel comp 8620 sleeve or steel comp 8630 sleeve or steel comp 8640 sleeve or steel comp 8740 sleeve steel comp e4340 stem or steel comp 4027 stem or steel comp 4037 stem or steel comp 4130 stem or steel comp 4140 stem or steel comp 4150 stem or steel comp 4340 stem or steel comp 4620 stem or steel comp 4815 stem or steel comp 6150 stem or steel comp 8615 stem or steel comp 8620 stem or steel comp 8630 stem or steel comp 8640 stem or steel comp 8740 stem

Material Specification:

Fs 66 federal specification single material response mechanical lockastm a331 assn standard single material response sleeveastm a331 assn standard single material response stem

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0