NSN 5320-01-355-1474

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-355-1474 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.8645 inches and 0.8845 inches **Head Style:** Err-090 **Head Height:** Between 0.0550 inches and 0.0650 inches Width Between Flats: Between 0.0791 inches and 0.0801 inches **Shank Diameter:** Between 0.1630 inches and 0.1635 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.3020 inches and 0.3220 inches Lubrication: Dry film **Grip Length:** Between 0.5575 inches and 0.8795 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.1640 inches **Shear Strength:** 95000 single pounds per square inch Material: Iron alloy 660 **Material Specification:** Ams 5731 assn standard single material response or ams 5737 military specification single material response **Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjc Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5320-01-355-1474

Pin-rivet - Page 2 of 2



Fiig:

A528u0

Mil-std (military Standard):

spec.