

View Online at <https://aerobasegroup.com/nsn/5320-01-355-7070>

Fastener Length:

1.1660 inches

Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

Between 0.2016 inches and 0.2026 inches

Shank Style:

Blind rivet, nut and bolt (assembly)

Head Major Diameter:

Between 0.2966 inches and 0.3016 inches

Expansion Device:

Serrated stem-type w

Grip Length:

Between 0.4070 inches and 0.4690 inches

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Material:

Steel comp 4130 bolt or steel comp 4140 bolt or steel comp 8740 boltsteel comp 4130 nut or steel comp 4140 nut or steel comp 8740 nutsteel comp 303 sleeve or steel comp 304 sleeve

Material Specification:

Mil-s-6758 military specification 1st material response bolt or mil-s-6758 military specification 2nd material response bolt or mil-s-6049 military specification 3rd material response boltmil-s-6758 military specification 1st material response nut or mil-s-5626 military specification 2nd material response nut or mil-s-6049 military specification 3rd material response nutqq-s-763 federal specification single material response sleeve

Surface Treatment:

Cadmium bolt or chromate boltcadmium nut or chromate nutcadmium sleeve

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response boltqq-p-416, type 2, cl 2 federal specification single treatment response nutqq-p-416, type 1, cl 3 federal specification single treatment response sleeve

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-s-6758 spec.