

View Online at <https://aerobasegroup.com/nsn/5320-01-355-9281>

**Head Style:**

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

**Shank Diameter:**

Between 0.2016 inches and 0.2026 inches

**Shank Style:**

Threaded self-plugging shank w/sleeve

**Head Major Diameter:**

Between 0.2966 inches and 0.3016 inches

**Expansion Device:**

Threaded stem

**Lubrication:**

Wax or cetyl alcohol or solid film

**Grip Length:**

Between 0.532 inches and 0.594 inches

**Features Provided:**

Self-locking

**Min. Tensile Strength (psi):**

14000 pounds per square inch

**Hardness Rating:**

39.0 rockwell c bolt and 46.0 rockwell c bolt 39.0 rockwell c nut and 46.0 rockwell c nut

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Material:**

Steel comp 4130 bolt or steel comp 4140 bolt or steel comp 8740 bolt steel comp 4130 nut or steel comp 4140 nut or steel comp 8740 nut steel comp 303 sleeve or steel comp 304 sleeve

**Material Specification:**

Mil-s-6758 military specification 1st material response bolt or mil-s-5626 military specification 2nd material response bolt or mil-s-6049 military specification 3rd material response bolt mil-s-6758 military specification 1st material response nut or mil-s-5626 military specification 2nd material response nut or mil-s-6049 military specification 3rd material response nut

**Surface Treatment:**

Cadmium bolt and chromate bolt cadmium nut and chromate nut cadmium sleeve

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification single treatment response bolt qq-p-416, type 2, cl 2 federal specification single treatment response nut qq-p-416, type 1, cl 3 federal specification single treatment response sleeve

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A040a0

**Mil-std (military Standard):**

Mil-s-6758 spec.