## NSN 5320-01-355-9284

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-355-9284 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.6775 inches and 0.6975 inches **Head Style:** Err-090 **Head Height:** Between 0.0640 inches and 0.0740 inches Width Between Flats: Between 0.0791 inches and 0.0801 inches **Shank Diameter:** Between 0.1890 inches and 0.1895 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.3570 inches and 0.3770 inches Lubrication: Cetyl alcohol **Grip Length:** Between 0.6825 inches and 0.6925 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 4350 pounds per square inch **Thread Size:** 0.1900 inches **Shear Strength:** 125000 single pounds per square inch Material: Nickel alloy 718 **Material Specification:** Ams 5662 assn standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Ams 5662 assn standard single treatment response **Thread Series Designator:** Unjf

Shelf Life:

N/a

## NSN 5320-01-355-9284

Pin-rivet - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A528u0