

View Online at <https://aerobasegroup.com/nsn/5320-01-356-0100>

Fastener Length:

0.9780 inches

Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

Between 0.2016 inches and 0.2026 inches

Head Major Diameter:

Between 0.2966 inches and 0.3016 inches

Expansion Device:

Serrated stem-type w

Grip Length:

Between 0.2200 inches and 0.2810 inches

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Material:

Steel comp 303 bolt or steel comp 304 boltsteel comp 4130 nut or steel comp 4140 nut or steel comp 8740 nutsteel comp 303 sleeve or steel comp 304 sleeve or steel comp 303se sleeve

Material Specification:

Mil-s-6758 military specification 1st material response bolt or mil-s-5626 military specification 2nd material response bolt or mil-s-6049 military specification 3rd material response boltmil-s-6758 military specification 1st material response nut or mil-s-5626 military specification 2nd material response nut or mil-s-6049 military specification 3rd material response nutqq-s-763 federal specification 1st material response sleeve or ams 5639 assn standard 2nd material response sleeve or ams 5641 assn standard 3rd material response sleeve

Surface Treatment:

Cadmium boltcadmium nut and chromate nutcadmium sleeve and chromate sleeve

Surface Treatment Specification:

Qq-p-416, type 2, cl2 federal specification single treatment response boltqq-p-416, type 2, cl 2 federal specification single treatment response nutqq-p-416, type 1, cl 3 federal specification single treatment response sleeve

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-s-6758 spec.