## NSN 5320-01-356-0104

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-356-0104 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.6275 inches and 0.6475 inches **Head Height:** Between 0.064 inches and 0.074 inches Width Between Flats: Between 0.0791 inches and 0.0806 inches **Shank Diameter:** Between 0.1885 inches and 0.1895 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.357 inches and 0.377 inches Lubrication: Cetyl alcohol **Grip Length:** Between 0.3075 inches and 0.3175 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 50.0 rockwell a head and 80.0 rockwell a head **Thread Size:** 0.190 inches **Shear Strength:** 95000 single pounds per square inch Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5320-01-356-0104

Pin-rivet - Page 2 of 2



Fiig:

A528u0