## NSN 5320-01-356-0109

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-356-0109 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.760 inches and 0.780 inches **Head Style:** Err-090 **Head Height:** Between 0.080 inches and 0.090 inches Width Between Flats: Between 0.0947 inches and 0.0967 inches **Shank Diameter:** Between 0.2485 inches and 0.2495 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.415 inches and 0.440 inches Lubrication: Cetyl alcohol **Grip Length:** Between 0.370 inches and 0.380 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 50.0 rockwell a head and 80.0 rockwell a head **Thread Size:** 0.250 inches **Shear Strength:** 95000 single pounds per square inch Material: Titanium alloy uns r56400 **Material Specification:** Ams4928 assn standard single material response or ams 4967 assn standard single material response **Thread Series Designator:** Unjf Shelf Life: N/a

--

**Unit Of Measure:** 

## NSN 5320-01-356-0109

Pin-rivet - Page 2 of 2



em			

No

Fiig:

A528u0