NSN 5320-01-356-0112

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-356-0112 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.6275 inches and 0.6475 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.0791 inches and 0.0806 inches **Shank Diameter:** Between 0.1885 inches and 0.1895 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.2966 inches and 0.3016 inches Lubrication: Solid film and cetyl alcohol **Grip Length:** Between 0.3075 inches and 0.3175 inches Thready Qty Per Inch (tpi): 32 **Hardness Rating:** 50.0 rockwell a head and 80.0 rockwell a head **Thread Size:** 0.190 inches **Shear Strength:** 125000 single pounds per square inch **Countersink Angle:** 100.0 degrees Material: Nickel alloy 718 **Material Specification:** Ams 5662 assn standard single material response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 5320-01-356-0112

Pin-rivet - Page 2 of 2



Fiig:

A528u0