NSN 5320-01-356-2558



Pin-rivet - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5320-01-356-2558 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.6350 inches and 0.6550 inches **Head Style:** Err-090 **Head Height:** Between 0.0800 inches and 0.0900 inches Width Between Flats: Between 0.0947 inches and 0.0967 inches **Shank Diameter:** Between 0.2490 inches and 0.2495 inches **Shank Style: Head Major Diameter:** Between 0.4100 inches and 0.4150 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** Between 0.2450 inches and 0.2550 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch **Thread Size:** 0.2500 inches **Shear Strength:** 95000 single pounds per square inch Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5320-01-356-2558

Pin-rivet - Page 2 of 2



Fiig:

A528u0