# NSN 5320-01-356-3211

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-356-3211



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 0.5650 inches and 0.5850 inches

#### Head Style:

Err-090

#### **Head Height:**

Between 0.064 inches and 0.074 inches

### Width Between Flats:

Between 0.0791 inches and 0.0806 inches

#### Shank Diameter:

Between 0.1885 inches and 0.1895 inches

#### Shank Style:

Pin-rivet, straight, threaded

### Head Major Diameter:

Between 0.357 inches and 0.377 inches

# Lubrication:

Cetyl alcohol

# Grip Length:

Between 0.2450 inches and 0.2550 inches

### Thready Qty Per Inch (tpi):

32

### Min. Tensile Strength (psi):

160000 pounds per square inch

### Hardness Rating:

50.0 rockwell a head and 80.0 rockwell a head

## Thread Size:

0.190 inches

### Shear Strength:

95000 single pounds per square inch

### Material:

Titanium alloy uns r56400

### **Material Specification:**

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

### **Thread Series Designator:**

Unjf

## Shelf Life:

N/a

#### Unit Of Measure:

---

# NSN 5320-01-356-3211

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

