
# NSN 5320-01-356-3214

Pin-rivet - Page 1 of 2



**Thread Class:** 

3a

Thread Direction:

**Right-hand** 

Identification Code Color:

Blue

#### Fastener Length:

Between 1.0025 inches and 1.0225 inches

#### Head Style:

Err-090

Head Height:

Between 0.0640 inches and 0.0740 inches

#### Width Between Flats:

Between 0.0791 inches and 0.0806 inches

#### Shank Diameter:

Between 0.1890 inches and 0.1895 inches

Shank Style:

### Head Major Diameter:

Between 0.3170 inches and 0.3570 inches

## Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

#### Grip Length:

Between 0.6825 inches and 0.6925 inches

#### Thready Qty Per Inch (tpi):

32

#### Min. Tensile Strength (psi):

160000 pounds per square inch

#### Thread Size:

0.1900 inches

#### Shear Strength:

95000 single pounds per square inch

#### Material:

Titanium alloy uns r56400

#### Material Specification:

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

#### **Thread Series Designator:**

Unjf

# Shelf Life:

N/a

### Unit Of Measure:

---



# NSN 5320-01-356-3214

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

