# NSN 5320-01-356-6179

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-356-6179



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 0.4895 inches and 0.5095 inches

#### Head Style:

Err-090

#### **Head Height:**

Between 0.0550 inches and 0.0650 inches

### Width Between Flats:

Between 0.0791 inches and 0.0801 inches

#### Shank Diameter:

Between 0.1630 inches and 0.1635 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.3060 inches and 0.3220 inches

### Lubrication:

Cetyl alcohol

## Grip Length:

Between 0.1825 inches and 0.1925 inches

### Thready Qty Per Inch (tpi):

32

# Min. Tensile Strength (psi):

2940 pounds per square inch

## Thread Size:

0.1640 inches

# Shear Strength:

125000 single pounds per square inch

## Material:

Nickel alloy 718

# Material Specification:

Ams 5662 assn standard single material response

# Surface Treatment:

Passivate

# Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

# Thread Series Designator:

Unjf

## Shelf Life:

N/a

# NSN 5320-01-356-6179

Pin-rivet - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

