
# NSN 5320-01-356-6187

Pin-rivet - Page 1 of 2





#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

# Fastener Length:

Between 1.490 inches and 1.510 inches

#### Head Style:

Err-090

#### Head Height:

Between 0.102 inches and 0.112 inches

### Width Between Flats:

Between 0.1270 inches and 0.1295 inches

#### Shank Diameter:

Between 0.3110 inches and 0.3120 inches

#### Shank Style:

Pin-rivet, straight, threaded

### Head Major Diameter:

Between 0.475 inches and 0.505 inches

# Lubrication:

Cetyl alcohol

# Grip Length:

Between 0.950 inches and 1.050 inches

### Thready Qty Per Inch (tpi):

24

### Min. Tensile Strength (psi):

160000 pounds per square inch

### Hardness Rating:

50.0 rockwell a head and 80.0 rockwell a head

## Thread Size:

0.312 inches

### Shear Strength:

95000 single pounds per square inch

### Material:

Titanium alloy uns r56400

### Material Specification:

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

### **Thread Series Designator:**

Unjf

# Shelf Life:

N/a

#### Unit Of Measure:

---

# NSN 5320-01-356-6187

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

