
# NSN 5320-01-356-6188

Pin-rivet - Page 1 of 2





#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

# Fastener Length:

Between 0.740 inches and 0.760 inches

#### Head Style:

Err-090

#### Head Height:

Between 0.102 inches and 0.112 inches

#### Width Between Flats:

Between 0.1270 inches and 0.1295 inches

#### Shank Diameter:

Between 0.3110 inches and 0.3120 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.475 inches and 0.505 inches

# Lubrication:

Cetyl alcohol

# Grip Length:

Between 0.245 inches and 0.255 inches

## Thready Qty Per Inch (tpi):

24

## Min. Tensile Strength (psi):

160000 pounds per square inch

## Hardness Rating:

50.0 rockwell a head and 80.0 rockwell a head

# Thread Size:

0.312 inches

## Shear Strength:

95000 single pounds per square inch

#### Material:

Titanium alloy uns r56400

## **Material Specification:**

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

## **Thread Series Designator:**

Unjf

## Shelf Life:

N/a

#### Unit Of Measure:

---

# NSN 5320-01-356-6188

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

