# NSN 5320-01-356-6199

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-356-6199



**Thread Class:** 

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 1.785 inches and 1.805 inches

#### Head Style:

Err-090

#### Head Height:

Between 0.130 inches and 0.140 inches

### Width Between Flats:

Between 0.1582 inches and 0.1617 inches

#### Shank Diameter:

Between 0.3735 inches and 0.3745 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.565 inches and 0.600 inches

## Lubrication:

Cetyl alcohol

# Grip Length:

Between 1.245 inches and 1.255 inches

### Thready Qty Per Inch (tpi):

24

### Min. Tensile Strength (psi):

160000 pounds per square inch

### Hardness Rating:

50.0 rockwell a head and 80.0 rockwell a head

# Thread Size:

0.375 inches

### Shear Strength:

95000 single pounds per square inch

### Material:

Titanium alloy uns r56400

### Material Specification:

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

### **Thread Series Designator:**

Unjf

# Shelf Life:

N/a

#### Unit Of Measure:

---

# NSN 5320-01-356-6199

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

