NSN 5320-01-356-6207

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-356-6207



Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 2.300 inches and 2.320 inches

Head Style:

Err-090

Head Height:

Between 0.178 inches and 0.188 inches

Width Between Flats:

Between 0.2207 inches and 0.2242 inches

Shank Diameter:

Between 0.4985 inches and 0.4995 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.735 inches and 0.770 inches

Lubrication:

Cetyl alcohol

Grip Length:

Between 1.620 inches and 1.630 inches

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

160000 pounds per square inch

Hardness Rating:

50.0 rockwell a head and 80.0 rockwell a head

Thread Size:

0.500 inches

Shear Strength:

95000 single pounds per square inch

Material:

Titanium alloy uns r56400

Material Specification:

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

NSN 5320-01-356-6207

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

