# NSN 5320-01-356-6211

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-356-6211



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 1.010 inches and 1.030 inches

#### Head Style:

Err-090

#### Head Height:

Between 0.080 inches and 0.090 inches

### Width Between Flats:

Between 0.0947 inches and 0.0967 inches

### Shank Diameter:

Between 0.2485 inches and 0.2495 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.415 inches and 0.440 inches

## Lubrication:

Cetyl alcohol

## Grip Length:

Between 0.620 inches and 0.630 inches

### Thready Qty Per Inch (tpi):

28

### Min. Tensile Strength (psi):

160000 pounds per square inch

### Hardness Rating:

50.0 rockwell a head and 80.0 rockwell a head

### Thread Size:

0.250 inches

### Shear Strength:

95000 single pounds per square inch

### Material:

Titanium alloy uns r56400

### Material Specification:

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

### **Thread Series Designator:**

Unjf

# Shelf Life:

N/a

## Unit Of Measure:

--

# NSN 5320-01-356-6211

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

