

View Online at <https://aerobasegroup.com/nsn/5320-01-357-9443>

Fastener Length:

Between 0.607 inches and 0.637 inches

Head Style:

Undercut pan no. 2

Head Height:

Between 0.080 inches and 0.090 inches

Shank Diameter:

Between 0.188 inches and 0.192 inches

Shank Style:

Self-plugging high clinch shank

Head Major Diameter:

Between 0.356 inches and 0.394 inches

Expansion Device:

Plain stem-type t

Grip Length:

Between 0.438 inches and 0.500 inches

Material:

Iron alloy 660 locking ring or steel comp 304 locking ringaluminum alloy 5056 sleevesteel comp 8740 stem

Material Specification:

Ams 5731 assn standard 1st material response locking ring or ams 5639 assn standard 2nd material response locking ringq-q-a-430 federal specification single material response sleeveams 6322 assn standard single material response stem

Surface Treatment:

Passivate locking ringchromate sleeve cadmium stem and chromate stem

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response locking ringmil-c-5541 military specification single treatment response sleeveqq-p-416, type 2, cl 2 federal specification single treatment response stem

Specification Data:

80205-nas9301 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A040a0

Mil-std (military Standard):

Mil-c-5541 spec.