NSN 5320-01-358-3678

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-358-3678 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.5025 inches and 0.5225 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.0791 inches and 0.0806 inches **Shank Diameter:** Between 0.1885 inches and 0.1895 inches **Shank Style: Head Major Diameter:** Between 0.2580 inches and 0.3050 inches Lubrication: Cetyl alcohol **Grip Length:** Between 0.1825 inches and 0.1925 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.1900 inches **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Iron alloy 660 **Material Specification:** Ams 5731 assn standard single material response or ams 5737 assn standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5320-01-358-3678

Pin-rivet - Page 2 of 2



Fiig:

A528u0