

View Online at <https://aerobasegroup.com/nsn/5320-01-359-4659>

Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

Between 0.1970 inches and 0.1990 inches

Shank Style:

Threaded self-plugging shank w/sleeve

Head Major Diameter:

Between 0.378 inches and 0.385 inches

Expansion Device:

Threaded stem

Lubrication:

Wax or cetyl alcohol or paraffin wax

Grip Length:

Between 0.470 inches and 0.531 inches

Features Provided:

Drive nut and self-locking

Hardness Rating:

50.0 rockwell a head and 80.0 rockwell a head

Shear Strength:

95000 single pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Special Features:

Surface of head powder blasted

Material:

Titanium alloy uns r56400 bolttitanium alloy uns r56400 nutsteel comp 303 sleeve or steel comp 304 sleeve or iron alloy 660 sleeve

Material Specification:

Ams 4928 assn standard single material response bolt or ams 4967 assn standard single material response boltams 4928 assn standard single material response nut or ams 4967 assn standard single material response nut

Surface Treatment:

Passivate sleeve

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response sleeve

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0