

View Online at <https://aerobasegroup.com/nsn/5320-01-359-4666>

Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

Between 0.2630 inches and 0.2635 inches

Shank Style:

Threaded self-plugging shank w/sleeve

Head Major Diameter:

Between 0.3898 inches and 0.3948 inches

Expansion Device:

Serrated stem-type w

Lubrication:

Wax or cetyl alcohol or paraffin wax or dry film

Grip Length:

Between 0.595 inches and 0.656 inches

Features Provided:

Self-locking

Min. Tensile Strength (psi):

95000 pounds per square inch

Hardness Rating:

50.0 rockwell a head and 80.0 rockwell a head

Shear Strength:

75000 single pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Special Features:

Drive nut included

Material:

Titanium alloy uns r56400 bolt titanium alloy uns r56400 nut steel comp 304 sleeve or iron alloy 660 sleeve

Material Specification:

Ams 4928 assn standard single material response bolt or ams 4967 assn standard single material response bolt ams 4928 assn standard single material response nut or ams 4967 assn standard single material response nut

Surface Treatment:

Passivate sleeve

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response sleeve

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0