

View Online at <https://aerobasegroup.com/nsn/5320-01-359-6984>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 0.9400 inches and 0.9600 inches

**Head Style:**

Err-090

**Head Height:**

Between 0.0640 inches and 0.0740 inches

**Width Between Flats:**

Between 0.07910 inches and 0.08060 inches

**Shank Diameter:**

Between 0.1885 inches and 0.1895 inches

**Shank Style:**

Pin-riquet, straight, threaded

**Head Major Diameter:**

Between 0.3570 inches and 0.3770 inches

**Lubrication:**

Cetyl alcohol, specification 305, hi-shear corp

**Grip Length:**

Between 0.6200 inches and 0.6300 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Thread Size:**

0.1900 inches

**Shear Strength:**

95000 single pounds per square inch

**Special Features:**

Wd means without defects

**Material:**

Titanium alloy uns r56400

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A528u0