## NSN 5320-01-361-2163

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-361-2163 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 2.503 inches and 2.523 inches **Head Style:** Flush countersunk **Shank Diameter:** Between 0.3735 inches and 0.3745 inches **Shank Style:** Err-090 **Head Major Diameter:** Between 0.5554 inches and 0.5604 inches **Grip Length:** Between 1.933 inches and 1.943 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch **Thread Size:** 0.375 inches **Shear Strength:** 95000 single pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Steel **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, tyii, cl3 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 73197-51-12-31 professional/industrial association specification Shelf Life: N/a **Unit Of Measure:** 

Demilitarization:

No

## NSN 5320-01-361-2163

Pin-rivet - Page 2 of 2



Fiig:

A528u0