## NSN 5320-01-361-2164

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-361-2164 **Thread Class:** За **Thread Direction:** Right-hand **Fastener Length:** Between 2.072 inches and 2.092 inches **Head Style:** Flush countersunk **Shank Diameter:** Between 0.2797 inches and 0.2807 inches **Shank Style:** Err-090 **Head Major Diameter:** Between 0.4210 inches and 0.4260 inches **Grip Length:** Between 1.682 inches and 1.692 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch **Thread Size:** 0.250 inches **Shear Strength:** 95000 single pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Steel **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, tyii, cl3 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 73197-hl220-8-27 professional/industrial association specification Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** No

## NSN 5320-01-361-2164

Pin-rivet - Page 2 of 2



Fiig:

A528u0